

A printing plant should not be a toxic plant.



TIME FOR CLEANER AIR.

EXTRACTSTAR SPRAY POWDER EXTRACTION SYSTEMS



More than 1000 Installations Worldwide!



EXTRACTSTAR ensures a clean and healthy working environment for your press operators. Redundant spray powder on the non-printed areas of the sheet, and free floating powder will be efficiently extracted by our TOP extractor. In addition, powder that would fall onto the ground under the press when printing small format sheets will be collected and extracted by the BOTTOM extractor of this highly efficient system.

AUTO MODE OPERATION

Extraction auto starts when press spray powder unit begins operation.

EFFICIENT!

MANUAL OPERATION

System can be utilized to clean and maintain presses after printing.

EFFECTIVE!

Unbeatable Top & Bottom Extraction!

Easy Powder Disposal

TECHNICAL SPECIFICATIONS

Power Specifications

- Requirements: 220V / 3 Phase / 50 or 60 Hz
- Output: 1.5 kW for both top and bottom unit

Air Specifications

- Volume: 24 m³ at 50 Hz for both top & bottom unit
- Static Pressure: 150 mm/Aq

Physical Specifications

- Dimensions: *Top* - 1420x820x600mm
Bottom - 1730x1240x630mm
- Weight: *Top* - 170kg, *Bottom* - 160kg

Authorised Dealer / Agent